FUNCTIONAL DEPENDENCY

The functional dependency is a relationship that exists between two attributes. It typically exists between the primary key and non-key attribute within a table.

1.
$$X \rightarrow Y$$

The left side of FD is known as a determinant, the right side of the production is known as a dependent.


For example:

Assume we have an employee table with attributes: Emp Id, Emp Name, Emp Address.

Here Emp_Id attribute can uniquely identify the Emp_Name attribute of employee table because if we know the Emp_Id, we can tell that employee name associated with it.

Functional dependency can be written as:

We can say that Emp Name is functionally dependent on Emp Id.



1. Trivial functional dependency

- \circ A \rightarrow B has trivial functional dependency if B is a subset of A.
- \circ The following dependencies are also trivial like: A \rightarrow A, B \rightarrow B

Example:

- 1. Consider a table with two columns Employee Id and Employee Name.
- 2. {Employee_id, Employee_Name} → Employee_Id is a trivial functional dependency as
- 3. Employee_Id is a subset of {Employee_Id, Employee_Name}.
- 4. Also, Employee_Id → Employee_Id and Employee_Name → Employee_Name are trivi al dependencies too.

NIGINEERA

2. Non-trivial functional dependency

- \circ A \rightarrow B has a non-trivial functional dependency if B is not a subset of A.
- \circ When A intersection B is NULL, then A \rightarrow B is called as complete non-trivial.

Example:

- 1. ID \rightarrow Name,
- 2. Name → DOB


RELATIONAL DECOMPOSITION

• When a relation in the relational model is not in appropriate normal form then the decomposition of a relation is required.

U. Salah Marah B. B.

- o In a database, it breaks the table into multiple tables.
- o If the relation has no proper decomposition, then it may lead to problems like loss of information.
- Decomposition is used to eliminate some of the problems of bad design like anomalies, inconsistencies, and redundancy.

Types of Decomposition



NONLOSS DECOMPOSITION Or (Lossless Decomposition)

- If the information is not lost from the relation that is decomposed, then the decomposition will be lossless.
- The lossless decomposition guarantees that the join of relations will result in the same relation as it was decomposed.
- The relation is said to be lossless decomposition if natural joins of all the decomposition give the original relation.

Example:

EMPLOYEE_DEPARTMENT table:

EMP_ID	EMP_NAME	EMP_AGE	EMP_CITY	DEPT_ID	DEPT_NAME
22	Denim	28	Mumbai	827	Sales
33	Alina	25	Delhi	438	Marketing
46	Stephan	30	Bangalore	869	Finance
52	Katherine	36	Mumbai	575	Production
60	Jack	40	Noida	678	Testing

The above relation is decomposed into two relations EMPLOYEE and DEPARTMENT

EMPLOYEE table:

EMP_ID	EMP_NAME	EMP_AGE	EMP_CITY
22	Denim	28	Mumbai
33	Alina	25	Delhi
46	Stephan	30	Bangalore
52	Katherine	36	Mumbai
60	Jack	40	Noida

DEPARTMENT table

DEPT_ID	EMP_ID	DEPT_NAME
827	22	Sales
438	33	Marketing
869	46	Finance
575	52	Production
678	60	Testing

Now, when these two relations are joined on the common column "EMP_ID", then the resultant relation will look like:

Employee ⋈ **Department**

EMP_ID	EMP_NAME	EMP_AGE	EMP_CITY	DEPT_ID	DEPT_NAME
22	Denim	28	Mumbai	827	Sales
33	Alina	25	Delhi	438	Marketing
46	Stephan	30	Bangalore	869	Finance
52	Katherine	36	Mumbai	575	Production
60	Jack	40	Noida	678	Testing
Opcomposition is Lossless join decomposition.					



